Space-Point Determination in the NA49 Vertex TPCs

R. Jeff Porter for the NA49 Collaboration

The first stage of particle tracking in the NA49 Time Projection Chambers is the determination of space-points within each detector volume. This process of "cluster finding" connects neighboring pixels (pad-time bins) with ADC values larger than some threshold value. From the charge distributions within these pre-clusters, one or more clusters are formed and assigned x-y positions used as space-points in the track reconstruction software. Efficient track-finding is dependent on the input of accurate space-points and their uncertainties as provided by the cluster-finding software.

The cluster-finding software previously used in NA49 reconstruction code identified clusters from projected charge distributions in the time (y) and pad (x) directions (1D X 1D). During the past year, this code was replaced by one that finds clusters directly in the 2D pad-plane.

The utility of the 2D approach was first illustrated in the upstream TPC, VTPC1, where the pad-layout design was optimized for the NA49 central Pb+Pb data using Monte Carlo studies of expected track populations[1]. Characteristics of the 2D shape of contiguous pixel hits (pre-clusters) were found to be associated with trajectories crossing the pad-planes at near optimal angles[2]. Such "golden" pre-clusters are processed quickly into final clusters. The xz projection (in a 5cm vertical slice) of golden pre-clusters is shown in Fig. 1a in which complete particle trajectories are clearly visible. The golden pre-clusters represent >50\% of all preclusters extracted from the raw data and about 85% of these are eventually included in tracks.

Again using only 2D-shape characteristics, the remaining (non-noise) pre-clusters are classified as either from merged hits or large-angle hits. Those likely being due to a merging of multiple clusters are split, if possible, into more than one space-point. Those pre-clusters that are charac-

teristic of being from trajectories at large angles to the pad direction can be handled differently in the track-finding code. A plot of x-z positions for these last two categories is shown in Fig. 1b. The merged-type pre-clusters (filled circles) coincide with the high track density region near the beam-gap while those associated with large crossings angles (open circles) show the patterns of such trajectories. This information, obtained solely from pre-cluster characteristics, provides position or dispersion detail that is useful to the track-finding code.




Figure 1: Positions of pre-clusters in NA49-VTPC1. Panel (a) shows only "golden" clusters. Panel (b) contains both likely merged (filled circles) pre-clusters and those likely from large-angle tracks (open circles).

References

- [1] H. Appelshauser, NA49 Internal Report, (1995)
- [2] T. Trainor, NA49 Internal Report (1996)